

CONTENT

- address view 3
 - URL..... 3
 - Method 3
 - URL Params..... 3
 - Required..... 3
 - Optional..... 3
 - Data Params..... 4
 - Success Response 4
 - Error Response 4
 - Sample Call 4
 - JQuery/Ajax..... 4
 - Curl..... 5
 - Notes..... 5
- address create 6
 - URL..... 6
 - Method 6
 - URL Params..... 6
 - Data Params..... 6
 - Required 6
 - Success Response 6
 - Error Response 6
 - Sample Call 7
 - JQuery/Ajax..... 7
 - Curl..... 7
 - Notes..... 8
- notes view 8
 - URL..... 8
 - Method 8
 - URL Params..... 8
 - Required..... 8
 - Optional..... 9
 - Data Params..... 9
 - Success Response 9
 - Error Response 9
 - Sample Call 10

- JQuery/Ajax..... 10
- Curl..... 10
- Notes..... 10
- tasks view..... 11
 - URL..... 11
 - Method 11
 - URL Params..... 11
 - Required..... 11
 - Optional..... 11
 - Data Params..... 11
 - Success Response 12
 - Error Response 12
 - Sample Call 13
 - JQuery/Ajax..... 13
 - Curl..... 13
 - Notes..... 13
- Events view 14
 - URL..... 14
 - Method 14
 - URL Params..... 14
 - Required..... 14
 - Optional..... 14
 - Data Params..... 15
 - Success Response 15
 - Error Response 15
 - Sample Call 15
 - JQuery/Ajax..... 15
 - Curl..... 16
 - Notes..... 16

ADDRESS VIEW

Fetches address data from the database. Data can be queried, sorted and you can choose the fields you want to get.

URL

`.../api_address_view.php`

METHOD

GET

URL PARAMS

REQUIRED

`username: USERNAME`

`password: PASSWORD`

`dbname: DBNAME`

Username, password and dbname for solution and database as provided by INTex Publishing to the customer. Don't pass this credentials on, don't publish them anywhere, keep them safe.

OPTIONAL

`fields: SQL list of fields to show, for example`

`fields: Vorname, Nachname`

`type: predefined lists of fields. If no fields and no type are specified, you get complete address data.`

Tel gives you address data and telephone and smartphone numbers,

Mail gives you address data and email and website address.

All combines address data, Tel and Mail.

`type: Mail`

`where: SQL query condition, for example`

`where: Ort="Eitorf"`

`orderby: SQL sort command, for example`

`orderby: Ort DESC`

DATA PARAMS

None.

SUCCESS RESPONSE

In case of a successful query you get the content of the queried data fields as JSON.

Code: 200

Content: {

```
"adressen": [  
  {  
    "Firma": "INtex Publishing GmbH & Co. KG",  
    "Abteilung": "Geschäftsführung",  
    "Vorname": "Martin",  
    "Nachname": "Böhmer",  
    "Strasse": "Jakobstraße 9",  
    "PLZ": "53783",  
    "Ort": "Eitorf"  
    ...  
  }  
]
```

ERROR RESPONSE

Connection failed: In case the database isn't available or the credentials username and/or password are incorrect.

Mysqli error: https://www.w3schools.com/php/func_mysqli_error.asp

No resulting data:

```
{  
  "adressen": []  
}
```

SAMPLE CALL

JQUERY/AJAX

```
$.ajax({  
  "method": "GET",
```

```
"url": "https://www.intex-
publishing.de/adressenplus/api_address_view.php?username=USERNAME&pas
sword=PASSWORD&dbname=DBNAME ",

"headers": {

    "Content-Type": "application/x-www-form-urlencoded"

},

"xhrFields": {

    "withCredentials": true

}

});
```

CURL

```
curl -i \

-H "Host: www.intex-publishing.de" \

-H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132
Safari/537.36" \

-H "Content-Type: application/x-www-form-urlencoded" \

-H "Accept: */*" \

-H "Accept-Encoding: gzip, deflate, br" \

-H "Accept-Language: de-DE,de;q=0.9,en-US;q=0.8,en;q=0.7" \

-L -v "https://www.intex-
publishing.de/adressenplus/api_address_view.php?username=USERNAME&pas
sword=PASSWORD&dbname=DBNAME"
```

NOTES

This API can be used in

- INTex Hausverwaltung PLUS
- INTex Adressen PLUS
- INTex Auftrag PLUS
- INTex Inventar PLUS
- INTex Rechnungseingang PLUS
- INTex Fuhrpark PLUS
- INTex Gebäude PLUS

ADDRESS CREATE

Creates new addresses with the data provided. All fields are accessible – be careful, since the API itself doesn't check the validity of any given input. Kurzname field should always be provided.

URL

.../api_address_create.php

METHOD

POST

URL PARAMS

None.

DATA PARAMS

REQUIRED

username: USERNAME

password: PASSWORD

dbname: DBNAME

Username, password and dbname for solution and database as provided by INtex Publishing to the customer. Don't pass this credentials on, don't publish them anywhere, keep them safe.

fields: list of db-fields

values: list of new values for new record

Example:

fields: Kurzname, Vorname, Nachname

values: "INtex", "Martin", "Böhmer"

SUCCESS RESPONSE

Code: 200

ERROR RESPONSE

Connection failed: In case the database isn't available or the credentials username and/or password are incorrect.

Mysqli error: https://www.w3schools.com/php/func_mysqli_error.asp

SAMPLE CALL

JQUERY/AJAX

```
var formData = new FormData();

formData.append("username", "USERNAME");

formData.append("password", "PASSWORD");

formData.append("dbname", "DBNAME");

formData.append("fields", "Kurzname, Vorname,Nachname");

formData.append("values", "\"Intex\", \"Martin\", \"Böhmer\"");

$.ajax({

    "method": "POST",

    "url": "https://www.intex-
publishing.de/adressenplus/api_address_create.php",

    "xhrFields": {

        "withCredentials": true

    },

    "data": formData,

    "processData": false,

    "contentType": false

});
```

CURL

```
curl -i -X POST \

-H "Host: www.intex-publishing.de" \

-H "Origin: chrome-extension://mmdjghedkfbdhbjhmfbbgjaihmmhkeg" \

-H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132
Safari/537.36" \

-H "Content-Type: multipart/form-data; boundary=----
WebKitFormBoundaryyOi2BvXQZ4FZpX3Z" \

-H "Accept: */*" \

-H "Accept-Encoding: gzip, deflate, br" \
```

INtex REST API – INtex Publishing

```
-H "Accept-Language: de-DE,de;q=0.9,en-US;q=0.8,en;q=0.7" \  
-F "username=USERNAME" \  
-F "password=PASSWORD" \  
-F "dbname=DBNAME" \  
-F "fields=Kurzname, Vorname,Nachname" \  
-F "values=\"INtex\", \"Martin\", \"Böhmer\"" \  
-L -v "https://www.intex-  
publishing.de/adressenplus/api_address_create.php"
```

NOTES

This API can be used in

- INtex Hausverwaltung PLUS
- INtex Adressen PLUS
- INtex Auftrag PLUS
- INtex Inventar PLUS
- INtex Rechnungseingang PLUS
- INtex Fuhrpark PLUS
- INtex Gebäude PLUS

NOTES VIEW

Fetches notes data from the database. Data can be queried, sorted and you can choose the fields you want to get.

URL

```
.../api_notes_view.php
```

METHOD

```
GET
```

URL PARAMS

REQUIRED

```
username: USERNAME
```

```
password: PASSWORD
```

```
dbname: DBNAME
```

Username, password and dbname for solution and database as provided by INtex Publishing to the customer. Don't pass this credentials on, don't publish them anywhere, keep them safe.

OPTIONAL

fields: SQL list of fields to show, for example

```
fields: Titel, Zustaendigkeit
```

where: SQL query condition, for example

```
where: Titel="Besuch"
```

orderby: SQL sort command, for example

```
orderby: Titel DESC
```

DATA PARAMS

None.

SUCCESS RESPONSE

In case of a successful query you get the content of the queried data fields as JSON.

Code: 200

Content:

```
{
  "notizen": [
    {
      "Titel": "Besuch",
      "Projekt": "2",
      "Datum": "2017-09-27",
      "Bearbeitungsstatus": "Erledigt"
    }
  ]
}
```

ERROR RESPONSE

Connection failed: In case the database isn't available or the credentials username and/or password are incorrect.

Mysqli error: https://www.w3schools.com/php/func_mysqli_error.asp

No resulting data:

```
{
  "notizen": []
}
```

```
}
```

SAMPLE CALL

JQUERY/AJAX

```
$.ajax({  
    "method": "GET",  
    "url": "https://www.intex-  
publishing.de/adressenplus/api_notes_view.php?username=USERNAME&passw  
ord=PASSWORD&dbname=DBNAME ",  
    "headers": {  
        "Content-Type": "application/x-www-form-urlencoded"  
    },  
    "xhrFields": {  
        "withCredentials": true  
    }  
});
```

CURL

```
curl -i \  
  
-H "Host: www.intex-publishing.de" \  
  
-H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)  
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132  
Safari/537.36" \  
  
-H "Content-Type: application/x-www-form-urlencoded" \  
  
-H "Accept: */*" \  
  
-H "Accept-Encoding: gzip, deflate, br" \  
  
-H "Accept-Language: de-DE,de;q=0.9,en-US;q=0.8,en;q=0.7" \  
  
-L -v "https://www.intex-  
publishing.de/adressenplus/api_notes_view.php?username=USERNAME&passw  
ord=PASSWORD&dbname=DBNAME"
```

NOTES

This API can be used in

- INTex Hausverwaltung PLUS
- INTex Adressen PLUS

- INtex Auftrag PLUS
- INtex Inventar PLUS
- INtex Rechnungseingang PLUS
- INtex Fuhrpark PLUS
- INtex Gebäude PLUS

TASKS VIEW

Fetches tasks data from the database. Data can be queried, sorted and you can choose the fields you want to get.

URL

```
.../api_tasks_view.php
```

METHOD

```
GET
```

URL PARAMS

REQUIRED

```
username: USERNAME
```

```
password: PASSWORD
```

```
dbname: DBNAME
```

Username, password and dbname for solution and database as provided by INtex Publishing to the customer. Don't pass this credentials on, don't publish them anywhere, keep them safe.

OPTIONAL

fields: SQL list of fields to show, for example

```
fields: Titel, Zustaendigkeit
```

where: SQL query condition, for example

```
where: Titel="Aufgabe"
```

orderby: SQL sort command, for example

```
orderby: Titel DESC
```

DATA PARAMS

None.

SUCCESS RESPONSE

In case of a successful query you get the content of the queried data fields as JSON.

Code: 200

Content:

```
{
  "aufgaben": [
    {
      "Titel": "Test",
      "Projekt": "1",
      "Prioritaet": "8",
      "Datum": null,
      "Bearbeitungsstatus": "In Arbeit",
      "Frist": null
    },
    {
      "Titel": "Test",
      "Projekt": "1",
      "Prioritaet": "8",
      "Datum": null,
      "Bearbeitungsstatus": "In Arbeit",
      "Frist": "2017-04-28"
    }
  ]
}
```

ERROR RESPONSE

Connection failed: In case the database isn't available or the credentials username and/or password are incorrect.

Mysqli error: https://www.w3schools.com/php/func_mysqli_error.asp

No resulting data:

```
{
```

```
    "aufgaben": []  
  }  
}
```

SAMPLE CALL

JQUERY/AJAX

```
$.ajax({  
  "method": "GET",  
  "url": "https://www.intex-  
publishing.de/adressenplus/api_tasks_view.php?username=USERNAME&passw  
ord=PASSWORD&dbname=DBNAME ",  
  "headers": {  
    "Content-Type": "application/x-www-form-urlencoded"  
  },  
  "xhrFields": {  
    "withCredentials": true  
  }  
});
```

CURL

```
curl -i \  
  
-H "Host: www.intex-publishing.de" \  
  
-H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)  
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132  
Safari/537.36" \  
  
-H "Content-Type: application/x-www-form-urlencoded" \  
  
-H "Accept: */*" \  
  
-H "Accept-Encoding: gzip, deflate, br" \  
  
-H "Accept-Language: de-DE,de;q=0.9,en-US;q=0.8,en;q=0.7" \  
  
-L -v "https://www.intex-  
publishing.de/adressenplus/api_tasks_view.php?username=USERNAME&passw  
ord=PASSWORD&dbname=DBNAME"
```

NOTES

This API can be used in

- INtex Hausverwaltung PLUS
- INtex Adressen PLUS
- INtex Auftrag PLUS
- INtex Inventar PLUS
- INtex Rechnungseingang PLUS
- INtex Fuhrpark PLUS
- INtex Gebäude PLUS

EVENTS VIEW

Fetches events data from the database. Data can be queried, sorted and you can choose the fields you want to get.

URL

```
.../api_events_view.php
```

METHOD

```
GET
```

URL PARAMS

REQUIRED

```
username: USERNAME
```

```
password: PASSWORD
```

```
dbname: DBNAME
```

Username, password and dbname for solution and database as provided by INtex Publishing to the customer. Don't pass this credentials on, don't publish them anywhere, keep them safe.

OPTIONAL

fields: SQL list of fields to show, for example

```
fields: Titel, Zustaendigkeit
```

where: SQL query condition, for example

```
where: Titel="Weihnachten"
```

orderby: SQL sort command, for example

```
orderby: Titel DESC
```

DATA PARAMS

None.

SUCCESS RESPONSE

In case of a successful query you get the content of the queried data fields as JSON.

Code: 200

Content:

```
{
  "termine": [
    {
      "Titel": "Pfingstmontag",
      "Kalender": "Feiertag",
      "Datum": "2019-06-10",
      "Uhrzeit": "00:00:00"
    },
  ],
}
```

ERROR RESPONSE

Connection failed: In case the database isn't available or the credentials username and/or password are incorrect.

Mysqli error: https://www.w3schools.com/php/func_mysqli_error.asp

No resulting data:

```
{
  "aufgaben": []
}
```

SAMPLE CALL

JQUERY/AJAX

```
$.ajax({
  "method": "GET",
  "url": "https://www.intex-
publishing.de/adressenplus/api_events_view.php?username=USERNAME&pass
word=PASSWORD&dbname=DBNAME ",
  "headers": {
```

```
        "Content-Type": "application/x-www-form-urlencoded"
    },
    "xhrFields": {
        "withCredentials": true
    }
});
```

CURL

```
curl -i \
-H "Host: www.intex-publishing.de" \
-H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132
Safari/537.36" \
-H "Content-Type: application/x-www-form-urlencoded" \
-H "Accept: */*" \
-H "Accept-Encoding: gzip, deflate, br" \
-H "Accept-Language: de-DE,de;q=0.9,en-US;q=0.8,en;q=0.7" \
-L -v "https://www.intex-
publishing.de/adressenplus/api_events_view.php?username=USERNAME&pass
word=PASSWORD&dbname=DBNAME"
```

NOTES

This API can be used in

- INTex Hausverwaltung PLUS
- INTex Adressen PLUS
- INTex Auftrag PLUS
- INTex Inventar PLUS
- INTex Rechnungseingang PLUS
- INTex Fuhrpark PLUS
- INTex Gebäude PLUS